




EMS Electrodes

Diaphoretic, Foam, Single Use Electrode

Reference: **A10003-4-60**

Wet Gel



4 Electrodes / Pouch
600 Electrodes / Case

APPLICATION

Emergency Services

For: 24 Hours

PRODUCT INFORMATION

Shape	Circular
Size (excl. grip)	2.25 in / 57.15 mm
Sensor (Eyelet) Diameter	0.42 in / 10.592 mm
Substrate Thickness (adapter excluded)	0.063 in / 1.588 mm
Total Product Surface Area	3.5204 in ² / 89.4183 mm ²
Gel Area	0.3068 in ² / 7.7927 mm ²
Adhesive Area	3.2136 in ² / 81.6256 mm ²
Integrated Lead Wire (length / color)	N/A

MATERIALS

Substrate Material	Polyethylene Foam
Adhesive	Acrylic, Medical Grade
Gel Type	Conductive Wet Gel
Foam (Sponge) Material	Polyurethane Reticulated Foam
Release Liner	PS
Sensor Polymer	Ag/AgCl plated ABS
Adaptor / Connector (Stud)	Stainless Steel
Integrated Lead Wire Jacketing	N/A
Integrated Lead Wire Cord	N/A

ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

ACZ impedance (before defib simulation) @10 Hz	26 Ohm
DC Offset Voltage (before defib simulation)	0.39 mV
SDR Slope (remaining potential after defib) @ 30 Sec int.	0.06 mV/sec
ACZ impedance repeat (after defib simulation)	21 Ohm
COIIN (combined offset instability and inner noise)	6 µV
Bias Current Tolerance (DC offset voltage after DC loading)	6 mV

FEATURES

MR Conditional	No
X-ray Translucence	No
Integrated Abrader	No
Repositionability	No

PACKAGING

Product Packaging Material	Paper/PE/Foil/PE
Resealable Pouch	Yes
Product Packaging Size (L x W)	9 x 13 in 22.86 x 33.02 cm
Department Packaging - Box (L x W)	n/a in n/a cm
Transport Packaging - Carton (L x W)	14.5 x 10.875 x 6.75 in 36.83 x 27.623 x 17.145 cm

BIOCOMPATIBILITY

ISO 10993	Yes
Latex Free	Yes

ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)	None
Phthalate Derivatives Content (e.g. DEHP)	None
RoHS Compliant	Yes
REACH Compliant	Yes

SHELF LIFE

Product Shelf Life (in accordance with storage guidelines)	18 Months
--	-----------

REGULATORY STATUS

CE Mark according to MDD 93/42/EEC



Reorder Part Number: **6500008V**